

A1 INSTALLATION DRAWING


IF THIS DRAWING IS PRINTED IN HARDCOPY, IT IS FOR INFORMATION USE ONLY AND THEREFORE IS NOT SUBJECT TO UPDATING CONTROLS. ALWAYS REFER TO SOLIDWORKS VIEWER FOR LATEST ISSUE



THIS DRAWING IS CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT SHALL NOT BE LOANED OR COPIED OR DISCLOSED TO ANY OTHER PERSON OR USED FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN CONSENT OF AP RACING LTD.

AP Racing
 Coventry CV3 4LB
 Tel: +44 (0) 24 7663 9595
 Fax: +44 (0) 24 7663 9559
 e-mail: engineering@apracing.co.uk
 Web site: http://www.apracing.com

© AP Racing Ltd. 2005




18mm STROKE - INNER ROTATING RACE (HIGH SPEED)

ASSEMBLY NUMBER	FULCRUM DIAMETER	FULL STROKE	REPLACEMENT BEARING SUB. ASSY.
CP6859-38	38.0 (1.496")	18.0 (0.709")	CP3457-16
CP6859-50	50.0 (1.969")	18.0 (0.709")	CP3457-11
CP6859-54	54.0 (2.126")	18.0 (0.709")	CP3457-6

NOTE: LVDT VERSION OF CP6859-54 IS AVAILABLE - SEE CP6859-54LVDTCD DRAWING FOR DETAILS

THIS SLAVE CYLINDER FEATURES :
 THE BEARING IS HOUSED IN THE PISTON VIA THE OUTER RACE
 THE INNER RACE ROTATES, SUITABLE FOR HIGH SPEED APPLICATIONS.




12mm STROKE - INNER ROTATING RACE (HIGH SPEED)

ASSEMBLY NUMBER	FULCRUM DIAMETER	FULL STROKE	REPLACEMENT BEARING SUB. ASSY.
CP6859-1238-IN	38.0 (1.496")	12.0 (0.472")	CP3457-16
CP6859-1250-IN	50.0 (1.969")	12.0 (0.472")	CP3457-11
CP6859-1245-IN	45.0 (1.772")	12.0 (0.472")	CP3457-26
CP6859-1254-IN	54.0 (2.126")	12.0 (0.472")	CP3457-6

THIS SLAVE CYLINDER FEATURES :
 A SHORTENED STROKE SO AS TO REDUCE THE OVERALL LENGTH.
 THE BEARING IS HOUSED IN THE PISTON VIA THE OUTER RACE
 THE INNER RACE ROTATES, SUITABLE FOR HIGH SPEED APPLICATIONS.


ALL OTHER MOUNTING DIMENSIONS REMAIN THE SAME.




18mm STROKE - INNER ROTATING RACE (HIGH SPEED) FLAT FULCRUM

ASSEMBLY NUMBER	FULCRUM DIAMETER	FULL STROKE	REPLACEMENT BEARING SUB. ASSY.
CP6859-14	N/A	18.0 (0.709")	CP3457-22

THIS SLAVE CYLINDER FEATURES :
 THE BEARING IS HOUSED IN THE PISTON VIA THE OUTER RACE
 THE INNER RACE ROTATES, SUITABLE FOR HIGH SPEED APPLICATIONS.



ALL CONFIGURATIONS



DESCRIPTION

THE CP6859 SERIES CONCENTRIC SLAVE CYLINDER IS A LIGHTWEIGHT, HYDRAULICALLY SELF-CONTAINED UNIT WITH HIGH TEMPERATURE SEALS. ALL SEALING SURFACES ARE PROTECTED BY A HARD WEARING / LOW FRICTION COATING WHICH HELPS PROLONG SEAL LIFE.

ENSURE THAT THE UNIT IS INSTALLED AT THE SPECIFIED ANGLE, WITH THE BLEED PORT UPPERMOST. ALL FITTINGS INTENDED TO SEAT AT THE BOTTOM OF THE HYDRAULIC PORTS MUST HAVE AN INCLUDED ANGLE OF 90°

BODY MATERIAL: ALUMINIUM ALLOY (FORGED)
 PISTON MATERIAL: ALUMINIUM ALLOY

EFFECTIVE AREA: 920 mm² (1.426 sq."")
 MAXIMUM STROKE: REFER TO TABLE
 MAXIMUM PRESSURE: 8.6 N/mm² (1250 psi)

CALCULATED WEIGHTS
 CP6859-XX 381 g
 CP6859-12XX 257 g
 CP6859-12XX-IN 346 g

HYDRAULIC PORTS: M10x1.0x11.5 MIN. FULL THREAD
 HYDRAULIC FLUID: APR550 OR 600 BRAKE FLUID

REPLACEMENT SEAL KIT - CP3759-3

HYDRAULIC FITTING KIT (STEEL ADAPTOR 7/16" - 4") - CP3759-6
 HYDRAULIC FITTING KIT (STEEL ADAPTOR 3/8" - 3") - CP3759-5
 FITTINGS TO BE TIGHTENED TO 28 Nm (21 ft.lb)

NOTE:
 WHEN LARGE DIAMETER SPLINES ARE USED PLEASE CHECK CLEARANCE OF THE SPLINE IN THE SLAVE CYLINDER BODY.

LARGER SPLINES ALSO HAVE AN INCREASED DRIVEN PLATE HUB BOSS. PLEASE CHECK THE CLEARANCE OF THE DRIVEN PLATE AT MAXIMUM SLAVE TRAVEL. SEE THE CLUTCH ASSEMBLY INSTALLATION DRAWING FOR DETAILS.

MINERAL OIL VERSIONS OF ALL THE ASSEMBLIES ON THIS DRAWING ARE AVAILABLE FOR FURTHER INFORMATION PLEASE CONTACT AP RACING. SEE CP8084-1CD FOR MINERAL OIL COMPATIBLE ASSEMBLIES

Issue No.	Alterations		Zone	Initials
	Date & No.	Particulars		
1	04/01/12 C3988	FIRST ISSUE	#	JG
2	20/09/12 C3988	MINERAL OIL INSTALLATION DRAWING REFERENCE ADDED	A12	JG
3	05/04/13 C4477	CP6859-1245-IN ADDED	#	JG
4	13/05/13	Ø30.40 MIN ADDED	J9	JG
5	27/01/14 C4652	SAAB REFERENCE REMOVED	B12	JG
6	01/05/14 C4708	FITTINGS TO BE TIGHTENED TO 28 Nm (21 ft.lb) NOTE ADDED	#	JG
7	22/07/14 C4753	FLAT FULCRUM OPTION ADDED.	#	JG
8	04/03/15 C4867	Ø63.00 NOTE AND VEIW ADDED.	#	JG
9	23/03/16	CP6859-45 REMOVED FROM THE DRAWING.	#	JG
10	12/02/18 C5231	DRAWING SPLIT ONTO 2 SHEETS FOR INNER ROTATING AND OUTER ROTATING SLAVES CP6859-45 ADDED ONTO SHEET2	#	GS
11	19/03/18 C5231:02	SHEET1: FEED & BLEED NOTES ADDED SHEET2: CP6859-45 STROKE CORRECTED. 18mm WAS 12mm	L12 K13 E3	GS
12	18/06/18 RAC22280	R0.40 MAX. WAS R0.25 MAX.	L5	JCD
13	14/08/18	BLEED AND FEED PORTS CORRECTED	L12	OSM
14	20/11/19	CP6859-54-OUT ADDED TO SHEET 2	E1	CGT
15	26/03/20 C5377_02	CP6859-54:LVDT NOTE ADDED	K6	CGT
16	21/10/20 C5469_01	CP6859-45-IN REMOVED FROM DRAWING SHEET 1	K6	FL

SCALE 1:1 SHEET 1 OF 2

DRAWN: Jeremy Govan

APPROVED:

DERIVED FROM: CP3859-1CD

TITLE: CONCENTRIC SLAVE CYLINDER INSTALLATION DRAWING

DRG NO. CP6859-1CD

FOR OUTER ROTATING RACE SLAVE CYLINDERS SEE SHEET 2

A2 INSTALLATION DRAWING

If this document is printed in hardcopy, it is for information use only and therefore is not subject to updating controls. Always refer to viewer for latest issue.



THIS DRAWING IS CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT SHALL NOT BE LOANED OR COPIED OR DISCLOSED TO ANY OTHER PERSON OR USED FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN CONSENT OF AP RACING LTD.






AP Racing
Wheler Road
Coventry
CV3 4LB

Tel: +44 024 7663 9595
Fax: +44 024 7663 9559
e-mail: sales@ap racing.co.uk
Web site: http://www.ap racing.com



© AP Racing Ltd. 2012

Issue No.	Date & No.	Alterations Particulars	Zone	Initials
-	-	SEE SHEET 1 FOR ISSUE INFORMATION.	-	-



ALL CONFIGURATIONS

$\phi 63.00$ MAX
BODY DIAMETER OUTSIDE
SPIGOT LOCATION





18mm STROKE - OUTER ROTATING RACE

ASSEMBLY NUMBER	FULCRUM DIAMETER	FULL STROKE	REPLACEMENT BEARING SUB. ASSY.
CP6859-45	45.0 (1.772")	18.0 (0.709")	CP3457-19
CP6859-54-OUT	54.0 (2.126")	18.0 (0.709")	CP3457-10

THIS SLAVE CYLINDER FEATURES :
THE BEARING HOUSED ON THE PISTON VIA THE INNER RACE WITH THE OUTER RACE ROTATING.

ALL OTHER MOUNTING DIMENSIONS REMAIN THE SAME.



12mm STROKE - OUTER ROTATING RACE

ASSEMBLY NUMBER	FULCRUM DIAMETER	FULL STROKE	REPLACEMENT BEARING SUB. ASSY.
CP6859-1245	45.0 (1.772")	12.0 (0.472")	CP3457-19
CP6859-1250	50.0 (1.969")	12.0 (0.472")	CP3457-9
CP6859-1254	54.0 (2.126")	12.0 (0.472")	CP3457-10

THIS SLAVE CYLINDER FEATURES :
A SHORTENED STROKE SO AS TO REDUCE THE OVERALL LENGTH.
THE BEARING HOUSED ON THE PISTON VIA THE INNER RACE WITH THE OUTER RACE ROTATING.

ALL OTHER MOUNTING DIMENSIONS REMAIN THE SAME.

FOR INNER ROTATING RACE SLAVE CYLINDERS SEE SHEET 1

SCALE 1:1 SHEET 2 OF 2

DRAWN Jeremy Govan

APPROVED

DERIVED FROM

TITLE
CONCENTRIC SLAVE CYLINDER
INSTALLATION DRAWING

DRG NO. CP6859-1CD