P12.263

Issue: 5

If this document is printed in hardcopy, it is for information use only and therefore is not subject to updating controls. Always refer to viewer for latest issue.

FOR DISC REPLACEMENT REQUIREMENTS,

PLEASE ORDER KIT # CP6895-03M.CG12 *

FIRST ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT SHALL NOT BE LOANED OR COPIED OR DISCLOSED TO ANY OTHER PERSON OR USED FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN CONSENT OF AP RACING LTD.

AP Racing Wheler Road Coventry CV3 4LB RACING

© AP Racing Ltd. 2005

Tel: +44 024 7663 9595 Fax: +44 024 7663 9559 e-mail: sales@apracing.co.uk Web site:HTTP://www.apracing.com

AUDI S3 (06+) FRONT KIT NUMBER CP5575M1011

KIT NUMBER CF33/3MT011				
Ref	DESCRIPTION	QTY		
1	AUDI FRONT UPRIGHT	-		
2	CALIPER RIGHT HAND CALIPER LEFT HAND	1		
3	VENTED DISC RIGHT HAND VENTED DISC LEFT HAND	1		
4	MOUNTING BELL	2		
5	MOUNTING BRACKET 2			
6	0.5mm SHIM 12			
7	M12 x 70 CALIPER Mtg BOLT	4		
8	Ø18 CALIPER WASHER	4		
9	ANTI-RATTLE CLIP	2 2		
10	BRAIDED HOSE KIT	2		
11	BANJO (PART OF HOSE KIT)	2		
12	BANJO BOLT (PART OF HOSE KIT)	2		
13	GASKET (PART OF HOSE KIT)	4		
14	TOP HAT SLEEVE	22		
15	STEEL STRAP	66		
16	0.25UNF DISC MOUNTING BOLT	22		
17	0.25UNF STRAP MOUNTING BOLT	22		
18	ϕ 12.5 DISC WASHER	88		
19	0.25UNF NUT	44		
20	PAD SET (4)	2		
21	BLANKING HARNESS	2		
22	RETAIN OE BOLTS & WASHERS	4		
23	PAD RETAINER BOLTS	4		
24	PAD RETAINER SLEEVES	4		
25	RETAIN OE BRAKE HOSE BRAKET	2		
26	RETAIN OE M8 BOLT	2		

	BRAKE DISK WEAR			
	NEW	MIN WORN		
3	2.00mm	30.5mm		

RETAIN OE BRAKE HOSE CLIPS

Tightening Torques			
Part Ref #	Torque		
Bolt - Ref 7	68NM		
Bolt/Nut - Ref 16/17/19	14NM		
Banjo Bolt - Ref 12	25NM		
Pad Retaining Bolts - Ref 23	19NM		
Caliper Bleed Screws	17NM		
OE Bolts - Ref 22	To Manufactures Spec		

COMMENTS
Check caliper is central over disc, use 0.5mm shims (Part Ref 6) to adjust bracket if required, Note: disc assembly direction arrow illustration is of

right hand assembly.

This brake kit will not allow the use of the brake pad wear sensors found on OE pads.

PLEASE RETAIN THIS SHEET FOR FUTURE REFERENCE

(19) (18) (25) (26) (11` (23 [12] (14) 〔17[〕] **16** 15 100 0 01 REPLACE PAD WEAR SENSOR WIRING LOOM WITH THE BLANKING HARNESS SHOWN BELOW. ENSURE WIRES ARE THEN SECURED AWAY FROM ANY 00 · 0 0 ROTATING PARTS WHEN FITTED WITH TIE CLIP. THIS IS A PICTORIAL VIEW FOR REFERENCE ONLY. SOME PARTS MAY VARY FROM THOSE

NOTICE.

Drawn By: Nick Stevens

SUPPLIED. AP RACING RESERVE THE RIGHT TO CHANGE COMPONENTS WITHOUT PRIOR