



## Technical Data Sheet - Brake Caliper

This document applies only to the Brake Caliper with which this document was supplied and when not supplied as part of an AP Racing manufactured Brake Kit.

This brake caliper has been tested to specified parameters and the maximum operating parameters (shown below) should not be exceeded by the application on which this product is to be installed. It is the responsibility of the person specifying this product for a given application to ensure that the design parameters of the product are not exceeded, if in doubt please contact AP Racing technical department (roadtech@apracing.co.uk) with your vehicle details and an engineer will assess the suitability for you.

### This caliper is designed to operate within the following parameters

**Maximum Working Pressure**                      **130 bar ( 1900 psi)**  
**Maximum Brake Torque**                         **3900 Nm ( 2900 lbf.ft)**

Typical (maximum) Gross Vehicle Weight data has been provided in the following table. These examples assume the application to be a standard passenger vehicle fitted with road tyres and therefore deceleration rates above 13m/s<sup>2</sup> (1.3g) will not be achievable.

Typical Max. Vehicle GVW		
	Vehicle Configuration	
Caliper Installed Position	Front Engine	Rear Engine
Front Axle Application	2420 kg ( 5340 lbs)	2820 kg ( 6220 lbs)
Rear Axle Application	4230 kg ( 9330 lbs)	3380 kg ( 7450 lbs)